HARDOX® HiTuf

2020-11-17

The table shows available dimensions for direct order including the maximum length (mm)

Some restrictions, contact your local sales representative for more information

Only 1650 mm width, mill edges -0/+70 mm. Other dimensions must be approved by product manager Hardox®
For thermally cut edges, contact local sales force

Outside the range of dimensions

Minimum lenght: 2000 mm*)
Minimum quantities:

Thickness:	Minimum position weight:
3.0-60.0	2.5 tons
60.1-100,0	3.5 tons
100.1-120.0	4.0 tons
120.1-	5.0 tons

Width (mm)	1000-	1351-	1501-	1601-	1650	1701-	1801-	1901-	2001-	2101-	2201-	2301-	2401-	2501-	2601-	2701-	2751-	2801-	2901-	3001-	3101-	3201-	3301-
Thickness (mm)	1350	1500	1600	1700		1800	1900	2000	2100	2200	2300	2400	2500	2600	2700	2750	2800	2900	3000	3100	3200	3300	3350
40.0-45	10400	14630	14630	14630	14630	14630	14630	14100	13400	12800	12300	11700	11300	10800	10400	10100	10100	9700	9400	9100	8800	8500	8400
45.1-50	9100	14630	14630	14630	14630	14100	13400	12700	12100	11500	11000	10600	10100	9800	9400	9100	9100	8700	8500	8200	7900	7700	7600
50.1-55	9000	14630	14400	13600	13600	12800	12100	11500	11000	10500	10000	9600	9200	9000	9000	9000	9000	7900	7700	7400	7200	7000	6900
55.1-60	8300	14100	13200	12400	12400	11800	11100	10600	10000	9600	9200	9000	9000	8900	8600	8300	8300	7300	7000	6800	6600	6400	6300
60.1-65	7600	11200	11200	11500	11500	10800	10300	9800	9300	9000	9000	8900	8500	8200	7900	7600	7600	6700	6500	6300			
65.1-70	7000	11200	11200	10700	12100	10100	9500	9100	9000	8900	8600	8200	7900	7600	7300	7000	7000	6200					
70.1-75	6500	11200	10600	10000	11300	9400	9000	9000	8700	8300	8000	7600	7300	7000	6800	6500							
75.1-80	6100	10600	9900	9400	10600	9000	9000	8500	8100	7800	7000	7100	6800	6600	6300	6100							
80.1-85	5900	10000	9300	8800	10000	8800	8400	8000	7600	7300	7000	6700	6400	6100	5900	5700							
85.1-90	5600	9400	9000	8300	9400	8300	7900	7500	7200	6800	6500	6300	6000	5800	5600	5400							
90.1-95	5200	9000	8800	7900	8900	7900	7500	7100	6800	6400	6200	6000	5700	5400	5200	5100							
95.1-100	5000	8900	8300	7500	8500	7400	7100	6700	6400	6100	5800	5600	5400	5100	5000	4800							
100.1-105	4700	8400	8000	7100	8000	7100	6700	6400	6100	5800	5500	5300	5100	4900	4700	4500							
105.1-110	4400	8000	7500	6800	7700	6700	6400	6000	5800	5500	5300	5000	4800	4700	4400	4300							
110.1-115	4200	7600	7200	6500	7300	6400	6100	5800	5500	5200	5000	4800	4600	4000	4200	4100							
115.1-120	4000	7300	6900	6200	7000	6100	5800	5500	5200	5000	4800	4600	4400	4200	4000	3900							
120.1-125	3900	7000	6600	5900	6800	5800	5500	5300	5000	4800	4600	4400	4200	4000	3900	3700							
125.1-130	3700	6700	6300	5700	6500	5600	5300	5000	4800	4600	4400	4200	4000	3800	3700								
130.1-135				5500	6300																		
135.1-140				5300	6000																		
140.1-145				5100	5800																		
145.1-150				4900	5600																		
150.1-155				4800	5400																		
155.1-160				4600	5300																		

*) Minimum length when ordering one single plate is 3700 mm. Minimum order quantity is 2 plates when order length is less than 3700 mm.

SSAB