

HARDOX® 400 PLATE

2025-05-22

The table shows available dimensions in mm for direct order including the maximum length.

Some restrictions, contact your local sales representative for more information

Outside the range of dimensions

Width	1000-	1351-	1501-	1601-	1701-	1801-	1901-	2001-	2101-	2201-	2301-	2401-	2501-	2601-	2701-	2751-	2801-	2901-	3001-	3101-	3201-	3301-
Thickness	1350	1500	1600	1700	1800	1900	2000	2100	2200	2300	2400	2500	2600	2700	2750	2800	2900	3000	3100	3200	3300	3350
3.2 - 3.9																						
4.0 - 4.7																						
4.8 - 6.0																						
6.1 - 6.7																						
6.8 - 7.7																						
7.8 - 8.7																						
8.8 - 10.0																						
10.1 - 25.0																						
25.1 - 26.0																						14600
26.1 - 27.0																					14200	14000
27.1 - 28.0																						
28.1 - 29.0																						
29.1 - 30.0																						
30.1 - 31.0																						
31.1 - 32.0																						
32.1 - 33.0	14200																					
33.1 - 34.0	13800																					
34.1 - 35.0	13400																					
35.1 - 36.0	13100																					
36.1 - 37.0	12700																					
37.1 - 38.0	12400																					
38.1 - 39.0	12000																					
39.1 - 40.0	11700																					
40.1 - 45.0	10400																					
45.1 - 50.0	9400																					
50.1 - 55.0	9000																					
55.1 - 60.0	8600	14100	13200	12400	11700	11100	10600	10100	9600	9200	9000	9000	8900	8600	8300	8300	7300	7000	6800	6600	6400	6300
60.1 - 65.0	7900	13000	11200	11200	10800	10300	9700	9300	9000	9000	8900	8500	8200	7900	7600	7600	6700	6500	6300			
65.1 - 70.0	7300	12100	11200	10700	10100	9500	9000	9000	8900	8600	8200	7900	7600	7300	7000	7000	6200					
70.1 - 75.0	6800	11300	10600	10000	9400	9000	9000	8700	8300	7900	7600	7300	7000	6800	6500							
75.1 - 80.0	6300	10600	9900	9400	9000	8900	8500	8100	7700	7400	7100	6800	6600	6300	6100							
80.1 - 85.0	5900	9900	9300	8800	8800	8400	8000	7600	7300	6900	6700	6400	6100	5900	5700							
85.1 - 90.0	5500	9400	9000	8300	8300	7900	7500	7200	6800	6500	6300	6000	5800	5500	5300							
90.1 - 95.0	5200	9000	8800	7900	7900	7400	7100	6700	6400	6200	5900	5700	5400	5200	5000							
95.1 - 100.0	4900	8900	8300	7500	7400	7000	6700	6400	6100	5800	5600	5300	5100	4900	4800							
100.1 - 105.0	4700	8400	7900	7100	7100	6700	6400	6100	5800	5500	5300	5100	4900	4700	4500							
105.1 - 110.0	4400	8000	7500	6800	6700	6400	6000	5800	5500	5200	5000	4800	4600	4400	4300							
110.1 - 115.0	4200	7600	7200	6500	6400	6100	5800	5500	5200	5000	4800	4600	4400	4200	4100							
115.1 - 120.0	4000	7300	6800	6200	6100	5800	5500	5200	5000	4800	4600	4400	4200	4000	3900							
120.1 - 125.0	3800	7000	6600	5900	5800	5500	5200	5000	4800	4500	4400	4200	4000	3800	3700							
125.1 - 130.0	3700	6700	6300	5700	5600	5300	5000	4800	4600	4400	4200	4000	3800	3700								
130.1 - 135.0																						
135.1 - 140.0																						
140.1 - 150.0																						
150.1 - 160																						

^{*)} Minimum length when ordering one single plate is 3700 mm. Minimum order quantity is 2 plates when order length is less than 3700 mm.

Minimum lenght: 2000 mm^{*)}

Minimum quantities:

Thickness: Min. position weight:
4.0-60.0 2.5 tons
60.1-100.0 3.5 tons
100.1-120.0 4.0 tons
120.1- 5.0 tons

HARDOX® 400 SHEET

The table shows available dimensions mm for direct order including maximum length.

Cut lengths with mill edges, black

Some restrictions, please contact product manager or Tech support

Outside the range of dimensions

Min. length 1500 mm
Min. bundle weight 2 tons

Width	950-	1001-	1201-	1251-	1301-	1501-	1526-	1551-	1576-	1601-	1626-
Thickness	1000	1200	1250	1300	1500	1525	1550	1575	1600	1625	1650
2.00 - 2.49											
2.50 - 2.99											
3.00 - 3.49											
3.50 - 3.99											
4.00 - 4.49											
4.50 - 4.79											
4.80 - 4.99											
5.00 - 5.99											
6.00 - 6.40											
6.41 - 6.50											
6.51 - 6.99											
7.00 - 8.00											
8.10 - 10.0											
10.1 - 25.0											
25.1 - 26.0											
26.1 - 27.0											

Min position weight is one coil (17 kg/width-mm) cut into cut to length sheets of the same thickness and width.
Delivery weight accuracy +/- 10 %, at least -2 tons / + 3 tons.